


Specifications

Model	SLK-10	SLK-15	SLK-20	SLK-25
Lifting Height:	3,50 m	5,00 m	6,50 m	7,90m
Measures Transport Position				
Height:	1,98 m	1,98 m	1,98 m	1,98 m
Length:	0,90 m	0,90 m	0,96 m	1,02 m
Width:	0,80 m	0,80 m	0,80 m	0,80 m
Measures Working Position				
Height	1,98 m	1,98 m	1,98 m	1,98 m
Length:	1,50 m	1,80 m	2,22 m	2,22 m
Width without lateral outrigger:	0,80 m	0,80 m	0,80 m	0,80 m
Width incl. lateral outriggermax:	2,22 m	2,22 m	2,22 m	2,22 m
Weights				
Chassis Standard Equipment:	158 kg	179 kg	229 kg ¹	252 kg ¹
8 Counterweights incl.Box	295 kg	316 kg	366 kg	389 kg
Payload				
Load center: 36 cm:	450 kg	360 kg	360 kg	300 kg
Standard Equipment				
Winch:		1-Gear Winch with 2 Cranks		
Loading Tool:		Standard Lifting Fork		
Lateral Outrigger:	Optional	Optional	Inclusive	Inclusive

¹Incl. lateral Outrigger (14 kg/Pair). Lateral Outrigger is standard equipment on SLK 20 and SLK 25.

Wheel Loads



Weight of Load:	100 kg	200 kg	300 kg	400 kg
Front axle per wheel:	200 kg	300 kg	400 kg	500 kg
Rear axle per wheel:	150 kg	150 kg	150 kg	150 kg